



FEATURES

- High Quality 2.5 GHz Splitter with High Isolation
- High Performance Internal PCB Board
- DC Power Passing to All Ports
- Die-Cast Zinc Housing with Built-in Ground Terminal
- 2-Way, 3-Way, and 4-Way Models Available
- Indoor Use Only

SPECIFICATIONS

PART NUMBER	WRF23-03490	WRF33-03502	WRF43-03503
MODEL	2-Way	3-Way	4-Way
ELECTRICAL CHARACTERISTICS			
INSERTION LOSS 5-860 MHz (dB)	6.0	11.0	13.5
INSERTION LOSS 950-2500 MHz (dB)	7.0	12.0	13.5
INPUT RETURN LOSS 5-47 MHz (dB)	10.0	10.0	10.0
INPUT RETURN LOSS 47-1000 MHz (dB)	10.0	10.0	10.0
INPUT RETURN LOSS 1000-2500 MHz (dB)	8.0	8.0	8.0
ISOLATION BETWEEN OUTPUTS 5-47 MHz (dB)	15.0	15.0	15.0
ISOLATION BETWEEN OUTPUTS 47-860 MHz (dB)	20.0	20.0	20.0
ISOLATION BETWEEN OUTPUTS 950-2500 MHz (dB)	16.0	16.0	16.0

NOTE: TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

© 2013 VERICOM Global Solutions