



PACKING
1 PC IN A ZIP BAG



CABLE MARKING

VERICOM OPTICAL FIBER CABLE (UL) E519838 TYPE OFNR 70°C RISER CABLE 1.8mm OM5 TIA-568-C.3 ROHS COMPLIANT BATCH NO XXM

P1		P2
1	_____	1
2	_____	2

***Note: All relevant materials are complied with RoHS directive.**

7	TRANSPARENT COIL CABLE TIE, LENGTH 40mm	1
6	L/N WITH TRANSPARENT LABEL 20*20mm	1
5	BLACK HEAT SHRINK TUBE Ø4.0*15mm	2
4	MARK RING, COLOR YELLOW (#1 & #2)	4
3	LC/UPC MM/ LIME GREEN HOUSING / BOOT COLOR: LIME GREEN TUBE COLOR: LIME GREEN	2 SET
2	MM, DX/ UL, OM5, 50/ 125, OD1.8*3.7mm, CORNING, JACKET LIME GREEN (PT373C). DRAWING NO. EQ00602C-022	L + 100mm
1	LC/UPC SM/ 1.0	4
No.	COMPONENT DESCRIPTION	Quantity

APPROVED			UNLESS OTHERWISE SPECIFIED: TOLERANCES 0 ~ 200 mm ± 10 mm 201 ~ 1000 mm ± 20 mm 1001 ~ 1500 mm ± 25 mm 1501 ~ 2100 mm ± 30 mm 2100 ↑ ± 40 mm
CHECKED			
DRAWING		TITLE	OPTICAL FIBER CABLE
DATE	06/14/20	ITEM NO.	PC08U50218RLG**M
CHECKED		UNIT: mm	

Length (L)	Bag	Quantity
1M	150*240*0.08mm	400
2M	150*240*0.08mm	300
3M	150*240*0.08mm	250
4M	150*240*0.08mm	200
5M	150*240*0.08mm	200
6M	150*240*0.08mm	160
7M	150*240*0.08mm	140
8M	150*240*0.08mm	130
9M	150*240*0.08mm	130
10M	150*240*0.08mm	120
11M	170*290*0.08mm	120

Length (L)	Bag	Quantity
12M	170*290*0.08mm	110
13M	170*290*0.08mm	100
14M	170*290*0.08mm	80
15M	170*290*0.08mm	70
20M	170*290*0.08mm	60
25M	170*290*0.08mm	50
30M	170*290*0.08mm	40
35M	170*290*0.08mm	40
40M	210*300*0.08mm	40
45M	210*300*0.08mm	30
50M	210*300*0.08mm	30

TRANSMISSION PERFORMANCE

Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-10 (FOCIS-10)

MECHANICAL


Connector Insertion Loss : 0.10dB max. (LC Multimode - Standard IL)
 Connector Return Loss : 26dB min. (OM5)
 Connector Durability : 500 Cycles

PHYSICAL

Storage and shipping temperature: -40°C to 70°C
 Operating and installation temperature: -20°C to 70°C

NOTE:

All relevant materials are RoHS Compliant.

APPROVED			UNLESS OTHERWISE SPECIFIED: TOLERANCES		
CHECKED			0 ~ 200 mm	± 10 mm	
DRAWING		TITLE	OPTICAL FIBER CABLE	201 ~ 1000 mm	± 20 mm
		DATE	06/14/20	ITEM NO.	PC08U50218RLG**M
		CHECKED		UNIT: mm	